



SUNOCO 2-CYCLE ENGINE OIL

OVERVIEW

SUNOCO 2-CYCLE ENGINE OIL is a superior quality ashless 2-cycle lubricant. Premium base stocks are blended with a modern ashless detergent additive package to provide fortification for maximum performance in outboard engines. It is pre-diluted for ease of mixing with gasoline and may also be used in injector systems.

FEATURES & BENEFITS

SUNOCO 2-CYCLE ENGINE OIL provides excellent lubricity and protection against scuffing and wear. It's ashless additive package controls deposit formation, is low odor and low smoke, and prevents piston ring and valve sticking.

TYPICAL PROPERTIES

PRODUCT CODE	9993
Viscosity, cSt @ 100 °C	7.60
CCS, cP (@ -25 °C)	5450
Pour Point, °C	-40
Sulfated Ash, wt.%	Nil
Color	Blue-Green
Flash Point, °C	65
TBN	3.60
Gravity, ° API	32.8

APPLICATIONS

SUNOCO 2-CYCLE ENGINE OIL is recommended for all leading outboard engines, including the latest high horsepower units. It also provides excellent performance in two-cycle engines of motorcycles, chain saws, lawn mowers and snowmobiles. It may be used at manufacturers' recommended fuel/oil ratios from 11:1 to 100:1.

SPECIFICATIONS

TCW-3