



SUNOCO FULL SYNTHETIC UNIVERSAL CVT FLUID

OVERVIEW

SUNOCO FULL SYNTHETIC UNIVERSAL CVT FLUID is a superior quality, high performance fluid designed for use in today's metal-belt continuously variable transmissions. Suitable for use in most CVT applications on today's market, SUNOCO FULL SYNTHETIC UNIVERSAL CVT FLUID provides superior protection for today's modern vehicles.

FEATURES & BENEFITS

SUNOCO FULL SYNTHETIC UNIVERSAL CVT FLUID is specifically designed for both belt and chain driven CVT's and employs the latest additive technology to provide superior protection in all driving conditions. It exhibits superior anti-wear protection, exceptional shear and oxidation stability, and outstanding low-temperature flow characteristics while ensuring optimum component protection

APPLICATIONS

SUNOCO FULL SYNTHETIC UNIVERSAL CVT FLUID is specifically designed to covers most all constantly variable transmission applications. This scientifically formulated product is comprised of premium base stocks and the latest additives to provide maximum protection and long life.

SPECIFICATIONS

Audi/VW TL 52180, TL 52516 • BMW EZL 799A • Daihatsu Ammix CVTF-DC, CVTF-DFE • FCA CVTF+4 • Ford WSS-M2C933-A, MERCON C, M2C928-A • GM/Saturn CVT, DEX-CVT • Honda HCF-2 • Hyundai/Kia SP CVT-1 • Mazda CVTF 3320 • Mercedes Benz 236.20 • Mitsubishi Dia Queen CVTF J1, CVTF J4, Diamond ATF SP III • Nissan NS-1, NS-2, NS-3 • Subaru e-CVTF, Lineartonic, CV-30, CVTF-II, High Torque CVTF, i-CVT F, i-CVT FG • Suzuki CVT Fluid Green1, Green2, CVTF 3320 • Toyota TC, FE, WS

TYPICAL PROPERTIES

Product Code	5473
Viscosity, cSt @ 40 °C	34.20
Viscosity, cSt @ 100 °C	7.30
Viscosity Index	186
Color	L2.0
Calcium, wt%	0.22
Phosphorous, wt.%	0.35
Specific Gravity	0.852