



SUNOCO DURATRANS 50W FULL SYNTHETIC TRANSMISSION OIL

OVERVIEW

SUNOCO DURATRANS 50W FULL SYNTHETIC TRANSMISSION OIL is a full synthetic, premium quality, SAE 50 heavy duty manual transmission lubricant designed to meet the rigorous demands of extended drain warranty requirements for both on and off highway equipment. It provides outstanding cleanliness, superior oxidation stability and excellent low temperature performance. It is formulated for stability under severe conditions and is suitable for use in transmissions and gear cases where API GL-1 through API GL-4 protection is recommended.

FEATURES & BENEFITS

SUNOCO DURATRANS 50W FULL SYNTHETIC TRANSMISSION OIL provides extended drain intervals, all season performance and extended gear life over conventional oils. Its excellent thermal stability and extreme pressure properties allow for high load capacity and high shear stability. SUNOCO DURATRANS 50W FULL SYNTHETIC TRANSMISSION OIL has excellent low temperature properties and protects against corrosion, oxidation, and sludge and varnish buildup and is compatible with typical automotive seals and gaskets.

TYPICAL PROPERTIES

| | |
|------------------------------|-------|
| Product Code | 6363 |
| SAE Viscosity Grade | 50W |
| Viscosity, cSt @ 40 °C | 140 |
| Viscosity, cSt @ 100 °C | 17.6 |
| Viscosity Index | 146 |
| Flash Point, °C | 235 |
| Pour Point, °C | -45 |
| Foaming Sequences I, II, III | Pass |
| Density @ 15°C | 0.876 |

APPLICATIONS

SUNOCO DURATRANS 50W FULL SYNTHETIC TRANSMISSION OIL is designed for heavy-duty manual transmissions requiring API GL-5 and MT-1 performance and where extreme pressure and shock loading are common.

SPECIFICATIONS

Eaton Roadranger (E500) • Mack TO-A Plus • ArvinMeritor O-81 • Navistar TMS-6816 • MIL-PRF-2105E • SAE J2360 • API GL-4/MT-1 • MANN 341 SL • Meritor ZF Freedomline • Volvo STD 97305 • ZF TE-ML 02L • Eaton PS-164 rev 7