



SUNOCO TH-G FLUID

OVERVIEW

SUNOCO TH-G FLUID is a, premium grade, exceptionally high quality universal tractor hydraulic fluid that makes use of renewable resources. Formulated with superior quality, re-refined Group II base oils, it is designed for use in final drives and hydraulic systems of all major brands of tractors and other farm equipment using a common fluid reservoir. SUNOCO TH-G FLUID incorporates the latest additive chemistry and fluid reclamation processes to provide maximum protection for all systems requiring a universal fluid.

FEATURES & BENEFITS

SUNOCO TH-G FLUID utilizes specially treated base stocks and has enhanced frictional properties that optimize clutch and PTO performance. It is designed to improve PTO chatter control and has excellent clutch and elastomers compatibility. It has a high viscosity index and is very shear stable while offering improved wet brakes control and excellent protection against rust, corrosion and yellow metal etching. SUNOCO TH-G FLUID has superior anti-wear and extreme pressure properties to protect key components.

APPLICATIONS

SUNOCO TH-G FLUID is designed for heavy duty transmissions, differentials, final drives, hydraulic systems, power steering systems, wet brakes, PTO's and hydrostatic drives. Suitable for top-up and re-fill of systems, SUNOCO TH-G FLUID is also used for certain commercial transmission applications requiring Type A (Suffix A) or Dexron fluids. Check your manual for your equipment's specific requirements. Do not use in passenger car automatic transmissions.

SPECIFICATIONS

API GL-4 • Allison Type C-4 • AGCO Power Fluid 821 XL • Case IH MS1210, MS1209, MS1207, MS1206, MS 1204-07/09 • Case New Holland (CNH) MAT-3509, 3525, 3506, 3505 • Caterpillar TO-2 • Dennison HF-0, HF-1, HF-2 • Fendt • Ford ESN M2C134-A/B/C/D, FNHA-2C-201.00, FNHA-2-C-200.00, M2C86-B/C, M2C41-B, M2C48-A/B • International Harvester B-6 Hy-Tran • John Deere J14B/C, J20A/B, J20C (Hygard), J21A • Kubota UDT Fluid • Massey Ferguson M1110, M1127B, M1129A, M1143, M1141 (Permatran III) • Minneapolis-Moline 35154, 35202, 35301 • Sauer-Sundstrand Hydrostatic Transmission Fluid • VALTRA G2-08 • VCE (Volvo) WB 101 • Vickers M-2950-S, I-286-S, 35VQ25 • White Farm Equipment Q-1705, Q-1722, Q-1766B, Q-1802 (Type 55 Fluid), Q-1826 (HTF) • ZF TE-ML 03E/05F/06E/06F/06K/17E/21F

TYPICAL PROPERTIES

Product Code	4023
Viscosity, cSt @ 40° C	57.5
Viscosity, cSt @ 100° C	9.20
Viscosity, cP @ -20° C	2,600
Viscosity, cP @ -35° C	20,500
Viscosity Index	155
Flash Point, °C	200
Pour Point, °F	-4.
Zinc, wt%	0.150
Density @ 15° C	0.89