



## SUNOCO TH-LT FLUID

### OVERVIEW

SUNOCO TH-LT FLUID is an exceptionally high quality universal tractor hydraulic fluid specially formulated using synthetic chemistry to provide outstanding low temperature characteristics under the coldest conditions. Designed to the same performance standards as our TH Fluid, SUNOCO TH-LT FLUID is intended for applications where a lower viscosity fluid is needed in all major brands of farm and off-road equipment that utilize a common fluid reservoir.

### FEATURES & BENEFITS

SUNOCO TH-LT FLUID utilizes special viscosity modifiers and synthetic componentry to provide excellent low temperature flow characteristics, and has enhanced frictional properties that optimize clutch and PTO performance. It is designed to improve PTO chatter control and has excellent clutch and elastomers compatibility. It has a high viscosity index and is very shear stable while offering improved wet brakes control and excellent protection against rust, corrosion and yellow metal etching. SUNOCO TH-LT FLUID has superior low temperature, anti-wear, and extreme pressure properties to protect key components.

### APPLICATIONS

SUNOCO TH-LT FLUID is designed for heavy duty transmissions, differentials, final drives, hydraulic systems, power steering systems, wet brakes, PTO's and hydrostatic drives. Suitable for top-up and re-fill of systems, SUNOCO TH-LT FLUID is also used for commercial transmission applications requiring Type A (Suffix A), Dexron and Type F fluids.

### SPECIFICATIONS

API GL-4 • Allison Type C-4 • AGCO Power Fluid 821 XL • Case IH MS1210, MS1209, MS1207, MS1206, MS 1204-07/09 • Case New Holland (CNH) MAT-3509, 3525, 3506, 3505 • Caterpillar TO-2 • Dennison HF-0, HF-1, HF-2 • Fendt • Ford ESN M2C134-A/B/C/D, FNHA-2C-201.00, FNHA-2-C-200.00, M2C86-B/C, M2C41-B, M2C48-A/B • International Harvester B-6 Hy-Tran • John Deere J14B/C, J20A/B, J20C (Hygard), J20D (Low Vis Hygard) J21A • Kubota Super UDT, UDT2 Fluids • Massey Ferguson M1110, M1127B, M1129A, M1143, M1141 (Permatran III) • Minneapolis-Moline 35154, 35202, 35301 • Sauer-Sundstrand Hydrostatic Transmission Fluid • VALTRA G2-08 • VCE (Volvo) WB 101 • Vickers M-2950-S, I-286-S, 35VQ25 • White Farm Equipment Q-1705, Q-1722, Q-1766B, Q-1802 (Type 55 Fluid), Q-1826 (HTF) • ZF TE-ML 03E/05F/06E/06F/06K/17E/21F

### TYPICAL PROPERTIES

Product Code	4233
Viscosity, cSt @ 40 °C	34.3
Viscosity, cSt @ 100 °C	7.4
Viscosity, cP @ -40 °C	11,500
Viscosity Index	190
Flash Point, °F	374
Pour Point, ° F	-60
Total Base Number	9.6
Zinc, wt%	0.149