



## SUNLUBE AW HYDRAULIC OILS

### OVERVIEW

SUNOCO SUNLUBE AW HYDRAULIC OILS are highly refined, good quality, general-purpose anti-wear hydraulic oils. These oils have good oxidation resistance, rust and corrosion protection and foam resistance. SUNOCO SUNLUBE AW SERIES HYDRAULIC OILS provide good wear protection for motors and other hydraulic system components.

### FEATURES & BENEFITS

SUNOCO SUNLUBE AW HYDRAULIC OILS have highly refined base oils and latest additive technology that provides solid AW performance for less critical applications. Their excellent price-to-value ratio and very good thermal and oxidation resistance provide the necessary protection to key components.

### TYPICAL PROPERTIES

	4003	4013	4033
Product Code	4003	4013	4033
Product	Sunlube AW 32	Sunlube AW 46	Sunlube AW 68
Viscosity, cSt @ 40 °C	32	46	68
Viscosity, cSt @ 100 °C	5.4	6.8	8.7
Viscosity Index	102	101	99
Flash Point, °F	405	410	450
Pour Point, ° F	0°	0°	+5
Color	1.0	1.5	1.5
Zinc, wt%	0.026	0.026	0.026
Cu Corrosion, 3 Hrs @100°C	1A	1A	1A
FZG Pass, Load Stage	10	10	10
Rust Test	Pass	Pass	Pass
Demulsibility	20	20	20
Oxidation Stability	3500+	3500+	3500+
Gravity, ° API	31.5	30.0	28.5

### APPLICATIONS

SUNOCO SUNLUBE AW HYDRAULIC OILS recommended applications include: hydraulic systems mining equipment, and moderately loaded gear sets, as well as general purpose lubrication.

### SPECIFICATIONS

Dennison HF-2 • Vickers I-286-S • Cincinnati Lamb P-68, P-69, P-70