



SUNOCO TACKY RED GREASE

OVERVIEW

SUNOCO TACKY RED is a premium lithium complex-based, high temperature grease containing extreme pressure and special additives for increased adhesion and resistance to water washout. This grease meets ASTM D-4950 service classification (NLGI GC-LB).

FEATURES & BENEFITS

SUNOCO TACKY RED has been formulated with select additives for outstanding high and low temperature performance and protects against wear, rust and corrosion. It has excellent thermal stability and oxidation resistance and a low coefficient of friction which improves mechanical life and reduces energy consumption.

TYPICAL PROPERTIES

Product Code	7223	9403
NLGI Consistency	#1	#2
Soap Type	Lithium Complex	Lithium Complex
Color	Red	Red
Viscosity, cSt @ 40 °C	120	260
Viscosity, cSt @ 100 °C	10.5	19.5
Operating Temp Range, °F	-10° -220°	-30° -325°
Penetration 60 Strokes	325	280
Oil Separation	less than 5%	less than 5%
Oxidation Stability, psi loss, 100 hrs.	5	5
Dropping Point, °F	500° min.	550° min.
Timken OK Load	60 lbs. min.	60 lbs. min.
Four Ball EP, LWI	40 Kgf.	40 Kgf.
Four Ball EP, Weld Point	315 kg.	400 kg.
Four Ball EP, Scar diameter, mm	0.60	0.60
Rust Test	Pass	Pass

APPLICATIONS

SUNOCO TACKY RED is available in NLGI grades #1 and #2 and makes an outstanding general purpose automotive and heavy-duty vehicle grease for wheel bearings, disc brakes, and general automotive, truck & bus lubrication. It is also designed for use as an excellent multi-purpose grease for industrial/commercial plant lubrication, agricultural equipment, and any other applications requiring a high quality, lithium complexed, extreme pressure fortified grease.

SPECIFICATIONS

NLGI GC-LB