



## SUNOCO ROCK DRILL OILS

### OVERVIEW

SUNOCO ROCK DRILL OILS are heavily compounded oils designed for the lubrication of pneumatic equipment exposed to excessive moisture or water spray. They are manufactured using premium quality mineral oils and special additive packages designed for heavy-duty rock drill applications. These additive systems employ excellent extreme pressure protection as well as rust and corrosion protection, tackiness, and antifoam properties.

### FEATURES & BENEFITS

SUNOCO ROCK DRILL OILS provide good adhesion to metal surfaces in the presence of moisture, have excellent extreme-pressure properties and offer exceptional protection against wear, rust, corrosion, and foaming.

### APPLICATIONS

SUNOCO ROCK DRILL OILS are recommended for and meet the general requirements of major manufactures of jack hammers, rock drills and other makes of pneumatic percussion equipment manufactured by Gardner-Denver, Ingersoll-Rand, and most others.

### TYPICAL PROPERTIES

Product Code	6313	6403	6223	6233	6243
ISO Viscosity Grade	68	100	150	220	320
Viscosity, cSt @ 40 °C	68	100	150	220	320
Viscosity, cSt @ 100 °C	8.7	10.8	12.0	19.3	24.0
Viscosity Index	99	98	93	96	95
Flash Point, °F	410	420	435	450	450
Copper Corrosion	1B	1B	1B	1B	1B
Timken EP	60	60	60	60	60
Falex Load Test, lbs.	2200	2200	2200	2200	2200
Steam Emulsion No.	1200+	1200+	1200+	1200+	1200+
Gravity, ° API	30.0	28.9	28.0	27.9	25.7