



SUNOCO SUPER C GOLD 15W-40 CK-4 DIESEL ENGINE OIL

OVERVIEW

SUNOCO SUPER C GOLD 15W-40 CK-4 DIESEL ENGINE OIL is a premium synthetic blend engine oil formulated to exceed the latest API diesel specifications as well as the warranty requirements of most manufacturers of diesel engines.

Designed for use in model year 2017 and newer heavy-duty diesel engines in high output service, as well as being fully backwards compatible to engines requiring any API C service class, SUNOCO @ SUPER C GOLD 15W-40 CK-4 provides robust protection, increased oxidation stability and excellent shear stability over any previous API category.

FEATURES & BENEFITS

SUNOCO @ SUPER C GOLD 15W-40 CK-4 uses carefully selected synthetic and premium conventional base stocks, the latest additive technology, and a superior star structure polymer to ensure it is built to withstand the rigors of today's severe service duty and provides improved performance over competitive products. SUNOCO @ SUPER C GOLD 15W-40 CK-4 can be used with complete success in over-the-road diesel trucks, off-highway diesel equipment, farm tractors, stationary equipment, and any vehicle or diesel engine where an API CK-4 or earlier C class oil is specified.

APPLICATIONS

SUNOCO SUPER C GOLD 15W-40 CK-4 DIESEL ENGINE OIL is recommended for use in the latest heavy-duty diesel engines in on-highway and off-highway applications including the long and short haul transportation, mining, construction, agriculture and marine industries. Its superior performance is suitable for use in gasoline engines requiring an API SN oil providing for use as a mix-fleet oil, as well as providing backwards serviceability for older diesel applications utilizing naturally aspirated designs. SUNOCO SUPER C GOLD 15W-40 CK-4 DIESEL ENGINE OIL can be used with confidence in foreign and domestic diesel-powered equipment and vehicles from a vast number of OEMs.

SPECIFICATIONS

API CK-4, CJ-4, CI-4, CI-4 PLUS, CH-4/SN, ACEA E9-16, E7-04 • Caterpillar ECF-3, ECF-2, ECF-1a • Cummins CES 20086, 20081, 20077 • Detroit Diesel 93K222, 93K218, 93K214 • Deutz DQC III-10 LA • Ford WSS-M2C171-F1 • JASO DH-2 • Mack EOS-4.5, EO-O Premium Plus, EO-N Premium Plus • MAN 3575 • Mercedes-Benz 228.31 • MTU MTL 5044 Type 2.1 • Renault RLD-4, RLD-3 • Volvo VDS-4.5 VDS-4, VDS-3

TYPICAL PROPERTIES

Product Code	3143
Viscosity, cSt @ 40 °C	120
Viscosity, cSt @ 100 °C	15.8
Viscosity Index	139
CCS, cP (@ -20 °C)	5500
HTHS @ 150 °C, cP	4.1
Flash Point, °C	229
Pour Point, °C	-40
Zinc, wt%	.127
Calcium, wt%	.105
Phosphorous, wt. %	.115
Sulfated Ash, wt. %	1.0
Total Base No.	10