



SUNOCO HEAVY-DUTY MV ATF

OVERVIEW

SUNOCO HEAVY-DUTY MV ATF is a top-tier, transmission fluid designed for use in a wide variety of heavy-duty automatic transmissions. Formulated to meet the requirements of modern heavy-duty automatic transmissions, **SUNOCO HEAVY-DUTY MV ATF** offers excellent shifting and power transfer performance and true wide-temperature operation.

FEATURES & BENEFITS

SUNOCO HEAVY-DUTY MV ATF has excellent frictional properties that ensure smooth shifting and power transfer in all operating conditions. It provides outstanding start up circulation and exceptional low and high temperature characteristics and it is specifically designed for heavy duty transmissions.

APPLICATIONS

SUNOCO HEAVY-DUTY MV ATF is specifically designed for use in heavy-duty automatic transmissions but can be used in other higher viscosity ATF applications. This high-performance product is intended for severe duty, high temperatures, and heavy loads. Suitable and fully tested for use against Volvo Construction Equipment AT101 and recommended as a replacement fluid for AT102 where specified (check your equipment manual for support details and drain intervals).

SPECIFICATIONS

Allison C4 • BMW LT 71141; 2634; ETL-7045E; -8072B • Chrysler +3; +4 • Ford M; MV • GM III(H) • HMC / KIA SP-II; SP-III • Honda ATF Z1 • Jaguar Idemitsu K17 • JASO M315 Class 1A • Land Rover Texaco N402 • MAN 339 V1; 339 Z2; 339 Z11 • Mazda ATF M-III; ATF M-V • Mercedes 236.5; 6;.7; 236.9 ; 10; 11; ATF 3403 M-115 • Nissan Matic D; Matic J; Matic K • Subaru ATF, ATF-HP • Toyota T-III; T-IV; JWS 3309 • Voith H55.6335.XX (G607) • Volvo 97340; 97341 • VW/Audi G 052 025 (09M); G 052 990 (09A) • ZF TE-ML 03D; 04D; 14A; 14B; 16L; 16R; 17C; 20B; 25B

TYPICAL PROPERTIES

Product Code	2993
Viscosity, cSt @ 40 °C	37.91
Viscosity, cSt @ 100 °C	7.3
Viscosity, cP @ -40°C	< 19,000
Viscosity Index	150
Flash Point, °F	213
Pour Point, ° F	-42