



## SUNOCO TH FLUID

### OVERVIEW

**SUNOCO TH FLUID** is a premium, high quality universal tractor hydraulic fluid for use in transmissions, final drives and hydraulic systems of all major brands of tractors and other farm equipment using a common fluid reservoir. This fluid incorporates the latest additive chemistry to provide maximum protection for all systems requiring a universal fluid.

### FEATURES & BENEFITS

**SUNOCO TH FLUID** has enhanced friction properties that optimize clutch and PTO performance, improves PTO chatter control and has excellent clutch and elastomers compatibility. It has a high viscosity index and is very shear stable while offering improved wet brakes control and excellent protection against rust, corrosion and yellow metal etching. **SUNOCO TH FLUID** has exceptional low temperature, anti-wear, and extreme pressure properties to protect key components.

### APPLICATIONS

**SUNOCO TH FLUID** is designed for heavy duty transmissions, differentials, final drives, hydraulic systems, power steering systems, wet brakes, PTO's and hydrostatic drives. Suitable for top-up and re-fill of systems, **SUNOCO TH FLUID** is also used for certain commercial transmission applications requiring Type A (Suffix A) or DEXRON® fluids. Check your manual for your equipment's specific requirements. Do not use in passenger car automatic transmissions.

### SPECIFICATIONS

**API GL-4 • Allison Type C-4 • AGCO Power Fluid 821 XL • Case IH MS1210, MS1209, MS1207, MS1206, MS 1204-07/09 • Case New Holland (CNH) MAT-3509, 3525, 3506, 3505 • Caterpillar TO-2 • Dennison HF-0, HF-1, HF-2 • Fendt • Ford ESN M2C134-A/B/C/D, FNHA-2C-201.00, FNHA-2-C-200.00, M2C86-B/C, M2C41-B, M2C48-A/B • International Harvester B-6 Hy-Tran • John Deere J14B/C, J20A/B, J20C (Hygard), J21A • Kubota Super UDT Fluid • Massey Ferguson M1110, M1127B, M1129A, M1143, M1141 (Permatran III) • Minneapolis-Moline 35154, 35202, 35301 • Sauer-Sundstrand Hydrostatic Transmission Fluid • VALTRA G2-08 • VCE (Volvo) WB 101 • Vickers M-2950-S, I-286-S, 35VQ25 • White Farm Equipment Q-1705, Q-1722, Q-1766B, Q-1802 (Type 55 Fluid), Q-1826 (HTF) • ZF TE-ML 03E/05F/06E/06F/06K/17E/21F**

### TYPICAL PROPERTIES

PRODUCT CODE	4413
Viscosity, cSt @ 40°C	54.7
Viscosity, cSt @ 100°C	9.4
Viscosity, cP @ -20°C	4,000
Viscosity, cP @ -35°C	44,500
Viscosity Index	155
Pour Point	-44
Flash Point	432
Sulfated Ash, wt. %	1.48
Zinc, wt. %	.1547