



## SUNOCO FLEET SAE 15W-40 DIESEL ENGINE OIL

### OVERVIEW

**SUNOCO FLEET SAE 15W-40 DIESEL ENGINE OIL** is designed for older engines that require higher initial TBN due to use of higher sulfur fuels (500 ppm and above). **SUNOCO FLEET SAE 15W-40 DIESEL ENGINE OIL** can be used with complete success in over-the-road diesel trucks, off-highway diesel equipment, farm tractors, and passenger cars and light trucks with diesel, turbo-charged diesel engines, or gasoline engines and is backward compatible with previous API Oil Categories.

### FEATURES & BENEFITS

**SUNOCO FLEET SAE 15W-40 DIESEL ENGINE OIL** has excellent soot dispersancy and wear control while providing outstanding protection against wear and corrosion. Its superior formula reduces sludge, protects against varnish formation and has superior anti-oxidation characteristics and high temperature stability.

### APPLICATIONS

**SUNOCO FLEET SAE 15W-40 DIESEL ENGINE OIL** is designed to meet the performance requirements of diesel engine manufacturers such as Caterpillar, Cummins, Detroit Diesel, Ford, Mack, Navistar, and Volvo. It is also formulated to provide outstanding performance in modern marine high-speed diesel engines including Caterpillar, Cummins, Volvo, Yanmar and Daihatsu, as well as transmissions requiring Allison C-4.

### SPECIFICATIONS

**API CI-4, CH-/SL • Allison C-4 • Caterpillar ECF-2, ECF-1a, TO-2 • Cummins CES 20071/72/76/77/78 • Detroit Diesel series 92, DDC series 2000, DDC series 4000. DDC series 50, DDC series 92 • Mack EO-N, EO-M Plus • Volvo VDS-3, VDS-2, VDS • Global DHD-1 • ACEA E2/E5/B3/A3/E7**

### TYPICAL PROPERTIES

<b>Product Code</b>	<b>5023</b>
Specific Gravity	.8740
Viscosity, cSt @ 100°C	15.4
Viscosity, cSt @ 40°C	119
CCS, cP( @ -20°C)	6270
Flash Point, COC, °C, min.	218
Pour Point, °C, max.	-34
Calcium, Wt. (%)	.3580
Phosphorous, Wt. (%)	.1084
Zinc, Wt. (%)	.1190
Total Base No., (D2896)	10.2