



SUNOCO FULL SYNTHETIC 75W-90 GL-5

OVERVIEW

SUNOCO FULL SYNTHETIC 75W-90 GL-5 is a heavy-duty, extreme pressure gear lubricant which is recommended for hypoid and bevel gear sets used in most rear drive differentials.

APPLICATIONS

SUNOCO FULL SYNTHETIC 75W-90 GL-5 is intended for service fill, top-off and refill of hypoid and other drive axles usually found on high performance rear drive and four-wheel drive vehicles, which recommend API GL-5 gear lubricants. Meets or exceeds the API GL-5 and MIL-PRF-2105D.

FEATURES & BENEFITS

SUNOCO FULL SYNTHETIC 75W-90 GL-5 provides exceptional wear protection and oxidation control. Its wide temperature rating allows it to circulate quickly and lubricate critical parts at cold-start, while high in-service temperatures under load are easily handled without thermal breakdown. **SUNOCO FULL SYNTHETIC 75W-90 GL-5** is a long-life service product when compared to conventional counterparts.

SPECIFICATIONS

API GL-5 • MIL-PRF-2105D

TYPICAL PROPERTIES

Product Code	6393
SAE Viscosity	75W-90
Viscosity, cSt @ 100 °C	15.2
Viscosity, cSt @ 40 °C	100
Viscosity Index	160
Pour Point, °C	-37
Flash Point, °C	230
Foam Sequence I, II, II	PASS