



## SUNOCO A/F COOLANT

### OVERVIEW

**SUNOCO A/F COOLANT** is a conventional, green colored, ethylene glycol-based antifreeze for use automobiles and light duty trucks. It is formulated to provide protection to all engine metals, including aluminum, copper, solder, brass, cast iron, and steel, from rust and corrosion that can cause cooling system damage.

### APPLICATIONS

**SUNOCO A/F COOLANT** is designed for use wherever a conventional green antifreeze is recommended.

Concentrate and 50/50 versions available.  
50/50 = Protects down to -34°F and up to 265°F  
40/60 = Protects down to -62°F and up to 270°F  
30/70 = Protects down to -84°F and up to 276°F

### FEATURES & BENEFITS

**SUNOCO A/F COOLANT** protects against rust, corrosion, sludge clogging, freeze-ups, scale build-up and coolant boil-over. Designed for use in most automobiles and light trucks, it provides superior protection to cooling systems. Provides up to 2 years or 50,000 miles service life.

### SPECIFICATIONS

ASTM D3306, D-4985 • Chrysler MS 7170 • Ford ESE-M97B-44-A • GM 1825M, 1899M • TMC RP 302B

### TYPICAL PROPERTIES

<b>PRODUCT CODE</b>	<b>7163</b>
Color	Green
Specific Gravity 60/60°F	1.070 - 1.090
pH	10 - 11
Reserve Alkalinity (ml)	3.4 min.
Freeze Point (50% by vol.), °C/F, min.	-37/-34
Total Water, wt. %	54 max.
Total Glycois, wt. %	150 max.
Foam break time, sec.	5 max.
Silicon, ppm	250 max.
Chloride, ppm	25 max.

Philadelphia, PA • [orders@sunocolubes.com](mailto:orders@sunocolubes.com) • [www.sunocolubes.com](http://www.sunocolubes.com) • Tel:(800) 660-0761 • Fax:(215) 352-0140