



## SUNOCO HD LITHIUM COMPLEX 3% MOLY EP GREASE

### OVERVIEW

**SUNOCO HD LITHIUM COMPLEX 3% MOLY EP GREASE** is a high-performance, multipurpose, extreme-pressure, lithium complex grease developed for the severe lubrication requirements of construction and off-road equipment manufactured by all major equipment manufacturers. It is particularly recommended for use in all equipment operating under heavy or shock loads, including wheel loaders, motor graders and bulldozers.

### FEATURES & BENEFITS

**SUNOCO HD LITHIUM COMPLEX 3% MOLY EP GREASE** is manufactured with high-quality, viscous base oils, special polymers, and a lithium complex soap thickener. It contains 3% molybdenum disulfide, tackifier, EP and antiwear additives, and rust and oxidation inhibitors. **SUNOCO HD LITHIUM COMPLEX 3% MOLY EP GREASE** provides excellent corrosion and wear protection and is highly resistant to water washout in equipment operating under heavy shock loading and under wet conditions.

### APPLICATIONS

**SUNOCO HD LITHIUM COMPLEX 3% MOLY EP GREASE** is designed for chassis parts and wheel bearings of construction, mining and other heavy mobile equipment, as well as constant-velocity joints, universal joints, brake self-adjusting screws and clutch release bearings on heavy equipment. **SUNOCO HD LITHIUM COMPLEX 3% MOLY EP GREASE** can be used on tractor-trailer fifth wheels, heavily-loaded plain and rolling-element bearings in industrial and mobile equipment where there is a need for a high temperature, extreme-pressure grease with 3% molybdenum disulfide.

### TYPICAL PROPERTIES

Product Code	7233	9453
NLGI Consistency	#1	#2
Color	Gray	Gray
Soap Type	Lithium Complex	Lithium Complex
Molybdenum, wt.%	3.0	3.0
Dropping Point, °F	>500	>500
Worked 60 Strokes	310-340	265-295
Viscosity, cSt @ 40 °C	320	320
Rust Prevention	Pass	Pass
Copper Strip Corrosion	1b	1b
Water Washout	5% max	5% max
Timken OK Load, lb.	55	55
Weld Point	400	400
LWI	70	70