



## SUNOCO RED LITHIUM EP #2 GREASE

### OVERVIEW

**SUNOCO RED LITHIUM EP #2** is a lithium 12-hydroxystearate based grease formulated from the highest quality base oils. Its extreme pressure additive system is fortified with a specialty rust and oxidation inhibiting system designed to outperform other "fighting grade" grease products.

### APPLICATIONS

**SUNOCO RED LITHIUM EP #2** has been designed as a cost-effective multi-purpose grease. It is suitable for a wide variety of applications and a wide variety of conditions. **SUNOCO RED LITHIUM EP #2** can be used in industrial environments, commercial applications, construction jobs, and agricultural operations in many roles. It can be used for lubricating wheel bearings, lynch pins, chassis points, machine parts and many other applications.

### FEATURES & BENEFITS

**SUNOCO RED LITHIUM EP #2** provides an extremely cost-effective product that combines a less expensive thickening agent with high quality additives in a combination designed to offer a superior performance-to-price ratio. Its specialty ingredients insure high film strength for lasting protection, extreme pressure additives for excellent wear protection and R&O componentry for unabated corrosion resistance.

### SPECIFICATIONS

NLGI #2

### TYPICAL PROPERTIES

<b>Product Code</b>	<b>9733</b>
NLGI Consistency	#2
Thickener Type	Lithium 12-hydroxystearate
Color	Red
Operating Temp Range	-10° to 220°F
Penetration, Worked 60 Strokes	265-295
Viscosity, cSt @ 40°C	180-220
Viscosity, cSt @ 100°C	15.5-17.5
Copper Strip Corrosion	1B
Oxidation Stability, psi loss 100 hrs.	5
Oil Separation, 24 Hrs 77°F	10%
Weld Point	250kg.
LWI	40
Scar Diameter	.45mm
Timken OK Load, Lbs.	45
Rust Prevention	PASS
Water Washout D1264	10%
Dropping Point	380°F, min.