



SUNOCO ANTIFREEZE

OVERVIEW

SUNOCO ANTIFREEZE is a conventional, green colored, ethylene glycol based antifreeze for use automobiles and light duty trucks. It is formulated to provide protection to all engine metals, including aluminum, copper, solder, brass, cast iron, and steel, from rust and corrosion that can cause cooling system damage.

FEATURES & BENEFITS

SUNOCO ANTIFREEZE protects against rust, corrosion, sludge clogging, freeze-ups, scale build-up and coolant boil-over. Designed for use in most automobiles and light trucks, it provides superior protection to cooling systems.

APPLICATIONS

SUNOCO ANTIFREEZE is designed for use wherever a conventional green antifreeze is recommended. Concentrate and 50/50 versions available.

50/50 = Protects down to -34° F and up to 265° F

40/60 = Protects down to -62° F and up to 270° F

30/70 = Protects down to -84° F and up to 276° F

SPECIFICATIONS

HEAVY DUTY: ASTM D-4985 • Caterpillar • Cummins 90T8-4 • GM 1899M • John Deere H24B1 • Mack Truck • Navistar B1 • SAE J1941 • TMC RP 302B • Volvo/GM Heavy Truck

AUTOMOBILE: ASTM D3306, D-4340 • Chrysler MS 7170 • Ford ESE-M97B-44-A • GM 1825M • John Deere H24C1 • SAE J1034

TYPICAL PROPERTIES

| | |
|-----------------------------|----------------------------|
| Boiling Point, 50 vol.%, °F | Concentrate 325° F Min. |
| Flash Point, °F | 250° F Min. |
| Reserve | 11 ml. Min. |
| pH, 50% Vol | 10.5 Min. - 11.0 Max. |
| Total Water, wt.% | 5% Max. |
| Total Glycois, wt.% | 95% Min. |
| Foam | 50 ml./3 sec. Max. |
| Silicon | 250 ppm., Max. |
| Specific Gravity 60/60° F | 1.120-1.130 |