



SUNOCO MOBILE GEO 15W-40

OVERVIEW

SUNOCO MOBILE GEO 15W-40 is a specially devised, high-quality oil for utilization in mobile gas engine oil (GEO) applications. Formulated with dispersant detergency technology and higher levels of antiwear additives than conventional low-ash GEO's, SUNOCO MOBILE GEO 15W-40 is designed to meet the demanding wear protection requirements of gas-conversion engines.

FEATURES & BENEFITS

SUNOCO MOBILE GEO 15W-40 provides outstanding oxidization, nitration, wear, and rust and corrosion protection. It provides superior protection under severe operating conditions while reducing sludge and deposits for long engine life and long service intervals.

TYPICAL PROPERTIES

Product Code	4393
SAE Viscosity Grade	15W-40
Viscosity Index	137
Viscosity, cSt @ 100 °C	15.2
Viscosity, cSt @ 40 °C	114
Viscosity, cP @ -20 °C	6300
Pour Point, °C(°F)	-36 (-33)
Flash Point (COC), °C (°F)	227 (441)
Zinc	0.088
Phosphorous, wt.%	0.08
Sulfated Ash, wt.%	.76
TBN	6.0

APPLICATIONS

SUNOCO MOBILE GEO 15W-40 is suitable for use in buses, transit fleets, trucks and other vehicles equipped with CNG or LPG engines.

SPECIFICATIONS

Cummins CES 20085 • Detroit Diesel PGOS 93K216 (Series 50G and 60G engines) • John Deere 6.8L and 8.1L CNG engines.