



## SUNOCO MORGO BEARING AND GEAR OILS

### OVERVIEW

SUNOCO MORGO BEARING AND GEAR OILS are high quality, high viscosity index backup roll bearing oils recommended for the lubrication of oil-film bearings on backup rolls in metal rolling mills. They are designed to meet the specifications of most bearing manufacturers. SUNOCO MORGO SERIES BEARING AND GEAR OILS are inhibited to protect bearing and journal surfaces against rust and corrosion and provide exceptional demulsibility.

### FEATURES & BENEFITS

SUNOCO MORGO BEARING AND GEAR OILS are effective over a wide temperature range and have excellent oxidation stability. They provide improved protection against corrosion, longer lubricant life, good resistance to foam, and unparalleled demulsibility.

### TYPICAL PROPERTIES

Product Code	7183	7193	7203	7213	72143
SAE Viscoisty Grade	100	150	220	320	460
Viscosity, cSt @ 40 °C	100	150	220	320	460
Viscosity, cSt @ 100 °C	11.0	15.2	18.7	24.0	30.3
Demulsibility	37	37	37	37	38
Viscosity Index	97	97	99	99	99
Flash Point, °F	233	238	243	249	257
Foaming Sequences I, II, III	Pass	Pass	Pass	Pass	Pass
Pour Point, ° F	0	5	5	10	15
Copper strip corrosion	1a	1a	1a	1a	1a
Demulsibility	25	25	25	25	25

### APPLICATIONS

SUNOCO MORGO BEARING AND GEAR OILS are designed specifically to meet the Super Demulsibility specification while providing extended lubrication life.

### SPECIFICATIONS

US Steel 135

Morgan Construction Co. MORGOIL® Advanced Bearing Lubricant

ARMCO Circulating Oil

MORGOIL® is a registered trademark of the Morgan Construction Company