



SUNOCO MULTI-PURPOSE ATF

OVERVIEW

SUNOCO MULTI-PURPOSE ATF is a premium automatic transmission fluid designed for new generation, electronically controlled transmissions. SUNOCO MULTI-PURPOSE ATF meets most major U. S. and import car manufacturers' performance requirements. This fluid was once licensed for the now obsolete General Motors DEXRON III-H and Ford Mercon requirements.

FEATURES & BENEFITS

SUNOCO MULTI-PURPOSE ATF utilizes high quality, highly refined base stocks for long service life and a superior additive system for protection of key transmission components. It contains specially formulated antioxidants and anti-wear agents, detergents and de-foaming agents, as well as special friction modifiers and lubricity agents for smooth shifting over a wide range of driving conditions, temperatures, and transmissions designs

APPLICATIONS

SUNOCO MULTI-PURPOSE ATF is designed for make-up and refill in 2005 and earlier General Motors and Ford cars and light trucks. It also is recommended for make-up and refill in older vehicles requiring Mercon fluid, as well as Fords requiring an M2C138CJ or M2C166H fluid. SUNOCO MULTI-PURPOSE ATF can also be used for off-highway transmissions, power steering, and other hydraulic systems requiring an Allison C-4 fluid. Meets requirements of Allison TES-389. The product also meets the industrial hydraulic oil demands of Denison HF-O, Vickers vane and Sundstrand piston pumps.

SPECIFICATIONS

1974-2005 General Motors cars and light trucks
1988-1997 Ford and other vehicles requiring Mercon
1981 and later Fords requiring an M2C138CJ or M2C166H fluid.
Licenses G-34014/G34047

TYPICAL PROPERTIES

| | |
|-------------------------|--------|
| Product Code | 5053 |
| Viscosity, cSt @ 40 °C | 34.49 |
| Viscosity, cSt @ 100 °C | 7.62 |
| Viscosity, cP @ -40 °C | 15,400 |
| Viscosity Index | 175 |
| Flash Point, °F | 224 |
| Pour Point, °C | -41 |
| Color | Red |
| Gravity, ° API | 30.8 |