



SUNOCO MULTI-VEHICLE SYN-BLEND ATF

OVERVIEW

SUNOCO MULTI-VEHICLE SYNTHETIC BLEND ATF is a superior quality, synthetic blend fluid suitable for use in most planetary geared automatic transmissions on the market. It meets or exceeds many OEM specifications and provides exceptional protection for all driving conditions.

FEATURES & BENEFITS

SUNOCO MULTI-VEHICLE SYNTHETIC BLEND ATF is formulated with the latest additive technology and has shown outstanding performance in friction durability, shear and oxidation stability and provides longer service life with superior foam resistance, minimization of deposits and consistent shift performance. It protects against wear, allows for smoother shifting with less shudder, and outperforms most other conventional and synthetic blend ATF fluids.

TYPICAL PROPERTIES

Product Code	506
Viscosity, cSt @ 40 °C	32.0
Viscosity, cSt @ 100 °C	6.3
Viscosity Index	148
Viscosity, cP @ -40°C	12,500
Flash Point, °C	204
Pour Point, °C	-50
Color	Red
Gravity, ° API	33.2

APPLICATIONS

SUNOCO MULTI-VEHICLE SYNTHETIC BLEND ATF may be used in most automatic transmission applications including all GM, Ford, Chrysler, Toyota/Lexus, Nissan/Infinity, and Honda/Acura transmissions, as well as transmissions installed in all Hyundai, Isuzu, Volvo, Jaguar, Kia, Land Rover, Mazda, Mercedes, Mitsubishi, Porsche, BMW, MINI, SAAB, Subaru, Suzuki, and VW/Audi cars and light trucks.

SPECIFICATIONS

Designed for use in most planetary geared automatic transmission.
NOT for use in CVT, DCT, Type F applications. Not for sale in CA.