



SUNOCO PCMO EXTENDED LIFE COOLANT

OVERVIEW

SUNOCO PCMO EXTENDED LIFE COOLANT utilizes technologically advanced coolant chemistry and is compatible for use in all automobiles and light duty trucks regardless of make, model, year or original coolant. Its inhibitors help provide maximum cooling system protection and minimize rust and corrosion.

FEATURES & BENEFITS

SUNOCO PCMO EXTENDED LIFE COOLANT is compatible with all automobiles and light duty trucks and enables 150,000 mile or 5 year protection when a complete cooling system flush and fill is performed. Its phosphate and silicate free formula meets US OEM requirements, as well as those specified by Japanese and European OEM's. Meets the performance requirements of GM6277M (DEX-COOL®).

TYPICAL PROPERTIES

PRODUCT	Concentrate
Color	Yellow
Boiling Point, 50 vol.%, °F	325° F. Min.
pH, 50% Vol	7.5 Min. - 10.0 Max.
Flash Point, °F	250° F., Min.
Total Water, wt.%	5% Max.
Total Glycois, wt.%	95% Min.
Foam Test	50 ml./3 sec., Max.
Specific Gravity 60/60 °F	1.115-1.124

APPLICATIONS

SUNOCO PCMO EXTENDED LIFE COOLANT is designed for all modern and classic automobile and light duty trucks that require advanced rust and corrosion protection.

Concentrate and 50/50 versions available.

50/50 = Protects down to -34° F and up to 265° F

40/60 = Protects down to -62° F and up to 270° F

30/70 = Protects down to -84° F and up to 276° F

SPECIFICATIONS

ASTM D-3306, D-4340