



SUNOCO STEAM CYLINDER OIL

OVERVIEW

SUNOCO STEAM CYLINDER OILS are designed primarily for use in steam cylinders, gas compressor cylinders, and worm gear drives. They are compounded lubricants formulated with special fatty oils to provide superior lubrication throughout their life cycle.

FEATURES & BENEFITS

SUNOCO STEAM CYLINDER OILS are formulated with high viscosity index base oils. Compounded with a high-grade animal fatty oil for improved metal adhesion, these oils provide excellent lubrication even when in contact with steam of low-to-medium pressure and of wet-to-saturated quality.

TYPICAL PROPERTIES

PRODUCT CODE	6113
ISO Viscosity Grade	460
Density @ 60° F	7.43
Flash Point, °C	274
Viscosity, cSt @ 40 °C	460
Viscosity, cSt @ 100 °C	32
Viscosity, SUS @ 100° F	-
Viscosity, SUS @ 210° F	-
Viscosity Index	108
Pour Point, °C	-9
Color	L3
Fatty Oil, %	5
AGMA Grade	5

APPLICATIONS

SUNOCO STEAM CYLINDER OILS are recommended for stem cylinder lubrication over a wide variety of conditions and steam qualities. Widely used as lubricants for gas compressors having separate cylinder lubrication, SUNOCO STEAM CYLINDER OILS are especially recommended for use in wet conditions. Due to the compounding of these lubricants, they may be safely utilized in certain types of worm gear applications.