



## SUNOCO SUPER C 15W-40 CK-4 DIESEL ENGINE OIL

### OVERVIEW

SUNOCO SUPER C 15W-40 CK-4 DIESEL ENGINE OIL is formulated to meet or exceed the latest API diesel engine oil specifications as well as the warranty and performance requirements of most diesel engine manufacturers.

### FEATURES & BENEFITS

SUNOCO SUPER C 15W-40 CK-4 DIESEL ENGINE OIL can be used with complete success in over-the-road diesel trucks, off-highway diesel equipment, farm tractors, and passenger cars and light trucks with diesel engines, turbo-charged or non turbo-charged, where an API CK-4 or earlier C class oil is specified.

### APPLICATIONS

Designed for use in model year 2017 and newer heavy-duty diesel engines in high output service, as well as being fully backwards compatible to engines requiring any API C service class, SUNOCO SUPER C 15W-40 CK-4 DIESEL ENGINE OIL provides robust protection, increased oxidation stability and excellent shear stability over any previous API category.

### SPECIFICATIONS

API CK-4, CJ-4, CI-4, CI-4 PLUS, CH-4, CF-4 CF • ACEA E9-16, E9-08 & E7-04 • Caterpillar ECF-3, ECF-2, ECF-1a, TO-2 • Cummins CES 20086, 20081, 20077 & 20076 • Detroit Diesel 7SE270, PG PGOS, 93K222, 93K218, 93K214 • Deutz DQC III-10 LA • Ford WSS-M2C171-F1 • International Harvester / Navistar • JASO DH-2 • Mack EOS-4.5, EO-O Premium Plus, EO-N Premium Plus, EO-M, • MAN 3575 • Mercedes-Benz 228.31 • MTU MTL 5044 Type 2.1 • Renault VI RLD-4, RLD-3 • Volvo VDS-4.5, VDS-4, VDS-3, VDS-2

### TYPICAL PROPERTIES

Product Code	3123
Viscosity, cSt @ 100 °C	14.8
Viscosity, cSt @ 40 °C	111
Viscosity Index	139
CCS, cP (@ -20 °C)	5900
Flash Point, °C	229
Pour Point, °C	-39
Zinc, wt.%	.123
Calcium, wt.%	.254
Sulfated Ash, wt.%	1.0
Specific Gravity	0.880
Total Base No.	10.0
HT/HS cP @ 150 °C	4.1
Sulfur, wt.%	.360
Phosphorous, wt.%	.108