



SUNOCO ULTRA 80W-90 GL-4 GEAR OIL

OVERVIEW

SUNOCO ULTRA 80W-90 GL-4 GEAR OIL is a multipurpose, extreme pressure gear lubricant recommended for use in spiral bevel or hypoid gear axles and certain manual transmissions. This gear oil is intended for service fill, top-off and refill of hypoid and other drive axles which recommend API GL-4 gear lubricants.

FEATURES & BENEFITS

SUNOCO ULTRA 80W-90 GL-4 GEAR OIL provides good foam resistance, protects against rust and corrosion and has outstanding thermal and oxidation stability for long gear life.

TYPICAL PROPERTIES

Product Code	6023
SAE Viscosity Grade	80W-90
Viscosity, cSt @ 40°C	168
Viscosity, cSt @ 100°C	16
Viscosity Index	98
Flash Point °F	450
Pour Point °F	-30
Weight lb/gal	7.38
Gravity, °API	28.2
Rust Test	Pass
Copper strip corrosion	1
Foam test (ASTM D 892), foam volume, ml Sequences 1-3	TR/0

APPLICATIONS

SUNOCO ULTRA 80W-90 GL-4 GEAR OIL is suitable for use in manual transmissions and in drive axles with spiral bevel gears or with hypoid gears where a GL-4 gear lubricant is recommended.

SPECIFICATIONS

API GL-4