



## SUNOCO ULTRA FULL SYNTHETIC 75W-140 GL-5

### OVERVIEW

SUNOCO ULTRA FULL SYNTHETIC 75W-140 GL-5 is a fully synthetic drivetrain lubricant engineered to meet demanding performance requirements. Using the latest additive technology, SUNOCO ULTRA FULL SYNTHETIC 75W-140 GL-5 is suitable for use in applications ranging from limited slip passenger car to commercial vehicles operating under standard loads.

### FEATURES & BENEFITS

SUNOCO ULTRA FULL SYNTHETIC 75W-140 GL-5 has outstanding thermal and oxidation stability, shear stability, and provides superior protection in all but the most severe applications. Designed to protect against corrosion and wear protection, SUNOCO ULTRA FULL SYNTHETIC 75W-140 GL-5 offer exceptional performance throughout a variety of difficult traction situations.

### TYPICAL PROPERTIES

Product Code	6203
SAE Viscosity Grade	75W-140
Viscosity, cSt @ 100 °C	30
Viscosity, cSt @ 40 °C	224
Viscosity Index	175
Pour Point, °C	-40
Flash Point, °C	215

### APPLICATIONS

SUNOCO ULTRA FULL SYNTHETIC 75W-140 GL-5 is formulated for final drives and is designed for mixed fleet use in passenger cars, light trucks, and commercial vehicles not heavily loaded or requiring an extended drain interval. SUNOCO ULTRA FULL SYNTHETIC 75W-140 GL-5 is intended for service fill, top-off and refill of hypoid and other drive axles usually found on high performance rear drive and four wheel drive vehicles, which recommend API GL-5 gear or GL-5 limited slip lubricants.

### SPECIFICATIONS

API GL-5/MT-1 • Limited Slip • SAE J2360 • MIL-PRF-2105E • GO-J