



## SUNOCO ULTRA HIGH TEMP RED GREASE #2

### OVERVIEW

SUNOCO ULTRA HIGH TEMP RED GREASE #2 is a premium-quality, high temperature, EP fortified grease for severe applications.

A lithium complex base is combined with a proprietary polymer, select additives, and an extremely viscous base oil to formulate a grease that provides superior load handling capability at very high temperatures.

### FEATURES & BENEFITS

A dropping point of nearly 600 °F combined with high load carrying capabilities gives SUNOCO ULTRA HIGH TEMP RED GREASE #2 excellent wear protection as well as superior rust and corrosion protection. It has excellent pumpability, high load capacity, resistance to water washout and is formulated to withstand extreme temperatures.

### TYPICAL PROPERTIES

Product Code	7423
NLGI Consistency	#2
Dropping Point, °F	550
Viscosity, cSt @ 40 °C	620
Viscosity, cSt @ 100 °C	39.1
Viscosity Index	101
Soap Type	Lithium Complex
Rust Prevention	PASS
Oxidation Stability	3
Timken OK Load	70
Weld Point	400
Color	Red

### APPLICATIONS

SUNOCO ULTRA HIGH TEMP RED GREASE #2 was specifically designed for road paving equipment and other equipment operating at extreme temperatures in extreme environments. It is a multi-purpose grease and can be used in construction, mining, agricultural, and industrial applications operating under heavy or shock loading.