



SUNOCO ULTRA LIMITED-SLIP GEAR OIL

OVERVIEW

SUNOCO ULTRA LIMITED-SLIP GEAR OIL is a multipurpose, heavy-duty, extreme pressure gear lubricant which is recommended for hypoid and bevel gear sets used in most limited-slip rear drive differentials. This gear oil is intended for initial fill, top-off and refill of hypoid and other drive axles usually found on high performance rear drive and four wheel drive vehicles, which recommend API GL-5 limited-slip gear lubricants.

FEATURES & BENEFITS

SUNOCO ULTRA LIMITED-SLIP GEAR OIL's optimized formula prevents gear chatter and provides excellent anti-wear and load carrying capabilities. It has outstanding thermal and oxidation stability for long life, while its latest additive technology ensures smooth operation under all conditions.

TYPICAL PROPERTIES

Product Code	6123
SAE Viscosity Grade	80W-90
Viscosity, cSt @ 40 °C	160
Viscosity, cSt @ 100 °C	15.2
Viscosity Index	98
Flash Point, °F	415
Pour Point, ° F	-10
Oxidation stability	5.6
Demulsibility	86.3
Emulsion, ml	0.05
Rust Test	Pass
Copper strip corrosion (ASTM D130)	1b
Foam test (ASTM D 892), foam volume, ml Sequences 1-3	TR/0
Gravity, ° API	28.5

APPLICATIONS

SUNOCO ULTRA LIMITED-SLIP GEAR OIL is designed for final drives which utilize limited-slip clutches and friction discs and contains special friction modifiers and additives to eliminate chatter and offer smooth performance throughout a variety of difficult traction situations.

SPECIFICATIONS

API GL-5