



SUNOCO ULTRA MULTI-GRADE ENGINE OILS

OVERVIEW

SUNOCO ULTRA MULTI-GRADE ENGINE OILS are formulated using high quality base oils and additive packages for use in gasoline fueled engines. These oils are formulated for excellent wear protection and resist viscosity and thermal breakdown.

FEATURES & BENEFITS

SUNOCO ULTRA MULTI-GRADE ENGINE OILS offer excellent detergency for engine cleanliness, easy cold weather starting, and engine protection under a wide variety of operating conditions. Their superior formulas help reduce deposits, protect high-performance engines, and help reduce engine wear and corrosion.

TYPICAL PROPERTIES

Product Code	5043	5033
SAE Viscosity Grade	10W-40	20W-50
Viscosity, cSt @ 100 °C	15.5	18.5
Viscosity, cSt @ 40 °C	105	155
Viscosity, CCS, cP @ °C	6,400 (-25)	7,500 (-15)
Viscosity Index	150	150
NOACK, wt.%	13.5	6.0
HT/HS, cP @150°C	3.8	4.70
Flash Point, °C	200	200
Pour Point, °C	-45	-35
Phosphorous, Wt. (%)	0.075	0.075
Calcium, Wt. (%)	0.136	0.136
Zinc, Wt. (%)	0.082	0.082
Density	7.25	7.35

APPLICATIONS

SUNOCO ULTRA 10W-40 is recommended for use in gasoline fueled automobiles and light duty trucks where a higher viscosity oil is preferred or where API SN, SM, SL, SJ, or SH product is required. SUNOCO ULTRA GT 20W-50 is recommended for use in high performance engines found in race and rally driving. It has a higher viscosity that provides engines with full protection under higher operating speeds, temperatures, and other adverse conditions.

SPECIFICATIONS

API SN, SM, SL, SJ