



SUNOCO ULTRA SYNTHETIC BLEND GF-5 ENGINE OILS

OVERVIEW

SUNOCO ULTRA SYNTHETIC BLEND ENGINE OILS are specially formulated using synthetic and Group II base oils and high performance additive packages to provide superior performance in gasoline fueled and flex-fueled engines. These oils are formulated for excellent oxidation stability and low temperature properties to insure protection during cold starts.

FEATURES & BENEFITS

SUNOCO ULTRA SYNTHETIC BLEND ENGINE OILS are uniquely formulated and are proven to help extend engine life, protect against sludge and engine wear, and have high detergency to prevent the formulation of harmful deposits. SUNOCO ULTRA SYNTHETIC BLEND SERIES ENGINE OILS contain frictional reducing additives that allow them to be certified as API SN/Resource Conserving.

APPLICATIONS

SUNOCO ULTRA SYNTHETIC BLEND ENGINE OILS are recommended for most all modern passenger cars and light duty trucks and are backwards compatible with most engines manufactured in the last 100 years.

SPECIFICATIONS

API SN, SM, SL, SJ • ILSAC GF-5 • Ford WSS-M2C946-A • Ford WSS-M2C945-A • GM 6094M

TYPICAL PROPERTIES

Product Code	5903	5913	5923
SAE Viscosity Grade	5W-20	5W-30	10W-30
Density	7.16	7.17	7.25
Viscosity, cSt @ 100 °C	8.0	10.5	10.4
Viscosity, cSt @ 40 °C	47	60.7	62.5
Viscosity Index	141	163	158
HT/HS, cP @150 °C	2.7	3.1	3.0
Flash Point, °C	230	230	230
Pour Point, °C	-41	-41	-32
Calcium, Wt. (%)	0.136	0.136	0.136
Phosphorous, Wt. (%)	0.075	0.075	0.075
Zinc, Wt. (%)	0.082	0.082	0.082
NOACK, wt.%	13	14	10