



## SUNOCO ULTRA SYNTHETIC BLEND GL-5 GEAR OILS

### OVERVIEW

SUNOCO ULTRA SYNTHETIC BLEND GEAR OILS are multipurpose, heavy-duty, extreme pressure gear lubricants which are recommended for hypoid and bevel gear sets used in most rear drive differentials.

### FEATURES & BENEFITS

SUNOCO ULTRA SYNTHETIC BLEND GEAR OILS are specially formulated for final drives. These oils contain special friction modifiers and additives to eliminate "chatter", and offer smooth performance throughout a variety of difficult traction situations. Both 80W-140 and 75W-90 Gear Oils utilize a Polymethacrylate VM which imparts excellent low temperature properties.

### TYPICAL PROPERTIES

Product Code	6053	6043
SAE Viscosity Grade	75W-90	80W-140
ISO Viscosity Grade	220	460
Viscosity cSt @40 °C	105	222
Viscosity cSt @100 °C	15	30
Viscosity Index (D2270)	195	173
Flash Point, COC °F (D92)	460	465
Pour Point °F (D97)	-35	-10
Oxidation Stability	5.7	5.6
Rust Test (ASTM D665)	Pass	Pass
Copper strip corrosion (ASTM D130)	1	1
Foam test (ASTM D 892)	TR/0	TR/0
Agma Number	5EP	7EP

### APPLICATIONS

These gear oils are intended for service fill, top-off and refill of hypoid and other drive axles usually found on high performance rear drive and four wheel drive vehicles, which recommend API GL-5 gear lubricants. Meets or exceeds the API GL-5 and MIL-PRF-2105D.

### SPECIFICATIONS

API - GL-5, MT-1 • MIL-PRF-2105E