



## SUNVIS 2105

### OVERVIEW

SUNOCO SUNVIS 2105 is a multi-grade anti-wear hydraulic fluid. It has been designed for year-round service in mobile equipment operating at very low or widely varying ambient temperatures. It is recommended for use in mobile hydraulic equipment, including cherry pickers, backhoes, shovels, hydraulic cranes and extension ladders. It can be used in stationary hydraulic equipment operating at abnormally low temperatures. SUNOCO SUNVIS 2105 provides excellent lubricity and wear protection, oxidation and corrosion protection and detergency for system cleanliness.

### FEATURES & BENEFITS

SUNOCO SUNVIS 2105 is a non-conductive, multi-grade viscosity fluid for wide operating temperature ranges. Its excellent lubricity and wear protection prevent oxidation while providing superior corrosion protection and detergency. SUNOCO SUNVIS 2105 hydraulic oil has a high dielectric strength for use in electrical service bucket trucks as an insulating oil.\*

### TYPICAL PROPERTIES

PRODUCT CODE	4053
Viscosity, cSt @ 40 °C	47.0
Viscosity, cSt @ 100 °C	7.80
Viscosity Index	135
Flash Point, °F	360
Pour Point, ° F	-45
Acid #	0.8
Copper Corrosion	1A
Foam	Pass
Dielectric Strength	Kv 35+
Oxidation Stability, Hrs	5000
Zinc, wt%	0.04
Gravity, ° API	31.4

### APPLICATIONS

SUNOCO SUNVIS 2105 is designed for mobile hydraulic equipment, including cherry pickers, backhoes, shovels, hydraulic cranes and extension ladders, as well as any equipment operating at low temperatures.

### SPECIFICATIONS

Delaval • Denison • Dynex • Moog • Racine • Rexroth • Sundstrand • Towler • Vickers • U.S. Steel

*\*Dielectric strength measurement given at point of manufacture. Dielectric strength deteriorates rapidly with contamination from particulates and moisture; oil must be kept clean and dry at all times.*