



## SUNOCO SUPER C MONOGRADE DIESEL ENGINE OILS

### OVERVIEW

**SUNOCO SUPER C MONOGRADE DIESEL ENGINE OILS** are high quality low ash engine oils formulated for diesel engines where ash deposits are a problem. The low ash content reduces ash deposits and helps keep intakes clear.

### APPLICATIONS

**SUNOCO SUPER C MONOGRADE DIESEL ENGINE OILS** are high quality detergent motor oils recommended for diesel and gasoline engines manufactured by American, European, Japanese, Korean and other manufacturers from around the world.

### FEATURES & BENEFITS

**SUNOCO SUPER C MONOGRADE DIESEL ENGINE OILS** has excellent frictional properties that ensure smooth shifting and power transfer in all operating conditions. Its fully synthetic base stocks provide outstanding start up circulation and exceptional low and high temperature characteristics and it is specifically designed for heavy duty transmissions.

### SPECIFICATIONS

**SUNOCO SUPER C 30W/50W:** API CF-2<sup>(1)</sup> • SL

**SUNOCO SUPER C 40W:** API CF<sup>(1)</sup> • CF-2

**SUNOCO SUPER C 10W meets Allison C-4 & CAT TO-2**

<sup>(1)</sup> Obsolete API service category.

## TYPICAL PROPERTIES

Product Code	5403	5413	5313	5433
SAE Viscosity Grade	10	30	40	50
Viscosity, cSt @ 100 °C	6.8	11.5	15.0	20.0
Viscosity, cSt @ 40 °C	42.6	93.0	143.0	216
Viscosity Index	115	110	107	105
Pour Point, ° F	-33	-11	+5	+10
Sulfated Ash, wt. %	1.16	1.34	.88	1.34

Philadelphia, PA • [orders@sunocolubes.com](mailto:orders@sunocolubes.com) • [www.sunocolubes.com](http://www.sunocolubes.com) • Tel:(800) 660-0761 • Fax:(215) 352-0140

The data and OEM specifications listed are to the best of our knowledge accurate. This information listed is typical data and should not be considered a product standard nor a standard upon which acceptance or rejection of delivered product is to be based. It is the owner's responsibility to consult their equipment owner's manual and select the proper lubricant and viscosity grade for give application. This data is subject to change without notification