



SUNOCO ULTRA FULL SYN ULV ATF

OVERVIEW

SUNOCO ULTRA FULL SYN ULV ATF is an ultra-low, fully synthetic automatic transmission fluid designed for use in the latest generation of high-tech transmission and eMobility applications. It is formulated both as a multi-vehicle ATF for conventional vehicles and for electric hybrid vehicles with oil-cooled motors. **SUNOCO ULTRA FULL SYN ULV ATF** delivers exceptional transmission protection and performance while offering the hardware protection, electrical insulation, and material compatibility needed by modern vehicle designs.

APPLICATIONS

SUNOCO ULTRA FULL SYN ULV ATF is recommended for applications requiring a low or ultra-low viscosity ATF. Use where * DEXRON® ULV or MERCON® ULV are specified.

FEATURES & BENEFITS

SUNOCO ULTRA FULL SYN ULV ATF utilizes the latest technology to provide exceptional performance. Its full synthetic formula and specialty additive package ensure that it has the durability to provide outstanding performance under all service conditions. **SUNOCO ULTRA FULL SYN ULV ATF** provides exceptional performance in the key areas of anti-shudder control, smooth shifting and torque transfer, oxidation and thermal stability, foam resistance and long service life.

SPECIFICATIONS

See full applications listing for recommended usage.

*Registered trademarks of GM and Ford Motor Company.

TYPICAL PROPERTIES

PRODUCT CODE	5083
Viscosity, cSt @ 40°C	20.2
Viscosity, cSt @ 100°C	4.5
Viscosity Index	140
Viscosity, cP @ -40°C	4,900
Flash Point, COC °C, min.	204
Pour Point, °C, max.	-54

Philadelphia, PA • orders@sunocolubes.com • www.sunocolubes.com • Tel:(800) 660-0761 • Fax:(215) 352-0140