



## SUNOCO FULL SYN DEXRON®-VI/MERCON® LV ATF

### OVERVIEW

**SUNOCO FULL SYN DEXRON®-VI/MERCON® LV ATF** is a specifically engineered, fully synthetic, next generation low viscosity multi-vehicle ATF that is OEM licensed and approved against both GM DEXRON®-VI/MERCON® LV ATF specifications. This technologically advanced formulation provides optimum protection under the harshest driving conditions while providing maximum fuel efficiency and performance.

### FEATURES & BENEFITS

**SUNOCO FULL SYN DEXRON®-VI/MERCON® LV ATF** has excellent shear and oxidation stability, low foaming tendencies, exceptional wear resistance, and corrosion and pitting protection. Its synthetic based formulation provides for outstanding cold start circulation as well as high temperature handling and oxidative protection. **SUNOCO FULL SYN DEXRON®-VI/MERCON® LV ATF** is a thermally stable fluid that resists sludging and deposit formation to ensure a long performance life.

### APPLICATIONS

Suitable for use against a wide range of ATF specifications\*, **SUNOCO FULL SYN DEXRON®-VI/MERCON® LV ATF** is also backwards compatible for use in older GM vehicles that specify DEXRON® III H, DEXRON® III G, DEXRON® IID, DEXRON® II or DEXRON® fluids. This fluid is approved by General Motors under license number J-60195 and by Ford under license number MLV161105.

### SPECIFICATIONS

See guide for listing of suitable applications.

\*Not to be used for DCT or CVT applications. MERCON® V and SP not supported.

### TYPICAL PROPERTIES

PRODUCT CODE	5163
Color	Red
Density, @ 15°C	.844
Flash Point, COC °C	225
Viscosity, Cst @ 40°C	28.8
Viscosity, Cst @ 100°C	6.0
Viscosity Index	152
Viscosity, cP @ -40°C	11500
Pour Point, °C	-52

Philadelphia, PA • [orders@sunocolubes.com](mailto:orders@sunocolubes.com) • [www.sunocolubes.com](http://www.sunocolubes.com) • Tel:(800) 660-0761 • Fax:(215) 352-0140