



ULTRA[®]

dexos1[™] FULL SYNTHETIC MOTOR OILS

PRODUCT DATA

**API SQ/ILSAC GF-7 Oils are LIVE at
Sunoco Lubricants!**



ENHANCED FUEL ECONOMY



IMPROVED WEAR PROTECTION



ENHANCED ENGINE DURABILITY

SCAN TO



Become a Partner,
scan QR code
to learn more

LEARN MORE

ULTRA FULL SYNTHETIC dexos1[™] Gen3 SQ/GF-7A PASSENGER CAR ENGINE OILS

Specially formulated the Sunoco way, with Synthetic base oils and high-performance additive components.

Optimized for SQ/GF-7A Performance Standards while maintaining all the properties for backwards compatibility to all previous applicable API S and G (ILSAC) Performance Categories.

Designed to inhibit incidents of LSPI (low-speed pre-ignition), a combustion event that can cause premature wear or catastrophic failure.

ALL VISCOSITY GRADES - API SQ/ILSAC GF-7A CHRYSLER MS-6395
SAE 0W-20 - dexos1[™] Approved · FORD WSS-M2C972-A1 · HONDA · TOYOTA · MAZDA
SAE 5W-30 - dexos1[™] Approved · FORD WSS-M2C971-A1

TYPICAL PROPERTIES

PRODUCT CODES	5793	5933
SAE Viscosity Grade	0W-20	5W-30
Viscosity, cSt @ 100° C	8.2	10.2
Viscosity, CCS, cP @ ° C max	5,500 (-35)	5,000 (-30)
Pumping Vis, cP max	60,000	60,000
Flash Point, COC, °C, min	225	230
Density @ 15°C	0.87	0.87

