



## SUNOCO TACKY RED GREASE

### OVERVIEW

**SUNOCO TACKY RED** is a premium lithium complex-based, high temperature grease containing extreme pressure and special additives for increased adhesion and resistance to water washout. This grease meets ASTM D-4950 service classification (NLGI GC-LB).

### APPLICATIONS

**SUNOCO TACKY RED** is available in NLGI grades #1 and #2 and makes an outstanding general purpose automotive and heavy-duty vehicle grease for wheel bearings, disc brakes, and general automotive, truck & bus lubrication. It is also designed for use as an excellent multi-purpose grease for industrial/commercial plant lubrication, agricultural equipment, and any other applications requiring a high quality, lithium complexed, extreme pressure fortified grease.

### FEATURES & BENEFITS

**SUNOCO TACKY RED** has been formulated with select additives for outstanding high and low temperature performance and protects against wear, rust and corrosion. It has excellent thermal stability and oxidation resistance and a low coefficient of friction which improves mechanical life and reduces energy consumption.

### SPECIFICATIONS

#### NLGI GC-LB

### TYPICAL PROPERTIES

Product Code	7223	9403
NLGI Consistency	#1	#2
Soap Type	Lithium Complex	Lithium Complex
Color	Red	Red
Viscosity, cSt @ 40 °C	120	220
Viscosity Index, min.	90	90
Operating Temp Range, °F	-10°-350°	-30°-350°
Penetration 60 Strokes	310-340	265-295
Fretting Wear, wt. mg.	8.0 max.	8.0 max.
Water Washout, %	5.0 max.	5.0 max.
Dropping Point, °F	520° min.	520° min.
Timken OK Load, lbs., min.	60	60
Four Ball EP, LWI, Kgf, min	60	60
Four Ball EP, Weld Point, Kg, min.	500	500
Four Ball EP, Scar diameter, mm	0.50	0.50
Rust Prevention	Pass	Pass